



Numer produktu: 0212892

### piSTAMP Enhanced Blow-Off COAX® MICRO Ti05-2x2, 1/4"-1/4"

- Ultra-lightweight decentralized ejector with integrated release function
- Efficient and patented COAX® ejector with lower air consumption and faster response as compared to corresponding competitive products.
- Generic design and mounting interface, suitable for end-of-arm-tools and suction cup holders used in automotive press-shops.
- Release function based on Exhaust Block principle (EBR), suitable for fast cycle speeds.
- O-ring sealed vacuum port (non-threaded).

## Ogólne

Materiał	TPE, HNBR, PA66, POM, SS, CUZN, NBR
Poziom hałasu	71 dBA
Minimalna temperatura	0 - 50 °C
Waga	47 g

## Wydajność

Ciśnienie zasilania	0,3 - 0,7 MPa
Optymalne ciśnienie zasilania, maks.	0,5 MPa
Próżnia, maksymalna	81 -kPa

## Parametry pneumatyczne

Przepływ	1,3 NI/s
----------	----------

Ciśnienie zasilania MPa	Zużycie powietrza NI/s	Przepływ próżni (NI/s) dla różnych poziomów próżni (-kPa)											Maksymalne podciśnienie -kPa
		0	10	20	30	40	50	60	70	80	90		
0,5	0,64	0,7	0,63	0,52	0,39	0,26	0,15	0,11	0,06	0,015	0	81	

Ciśnienie zasilania MPa	Zużycie powietrza NI/s	Czas opróżniania (s/l) dla różnych poziomów próżni (-kPa)											Maksymalne podciśnienie -kPa
		10	20	30	40	50	60	70	80	90			
0,5	0,64	0,15	0,33	0,55	0,85	1,33	2,09	3,27	6,25	0	81		

## Rysunki wymiarowe

