



Numer produktu: 0208766

piSTAMP STX0785x2, 8-8mm

- Ultra-lightweight decentralized ejector with integrated release function
- Efficient and patented COAX® ejector with lower air consumption and faster response as compared to corresponding competitive products.
- Generic design and mounting interface, suitable for end-of-arm-tools and suction cup holders used in automotive press-shops.
- Release function based on Exhaust Block principle (EBR), suitable for fast cycle speeds.
- O-ring sealed vacuum port (non-threaded).

Ogólne

Materiał	TPE, HNBR, PA66, POM, SS, CUZN, NBR
Poziom hałasu	77 dBA
Minimalna temperatura	0 - 50 °C
Waga	49 g

Wydajność

Ciśnienie zasilania	0,3 - 0,7 MPa
Optymalne ciśnienie zasilania, maks.	0,5 MPa
Próżnia, maksymalna	84 -kPa

Parametry pneumatyczne

Przepływ	1,02 NI/s
----------	-----------

Ciśnienie zasilania MPa	Zużycie powietrza NI/s	Przepływ próżni (NI/s) dla różnych poziomów próżni (-kPa)											Maksymalne podciśnienie -kPa
		0	10	20	30	40	50	60	70	80	90		
0,5	1,02	0,47	0,41	0,36	0,3	0,25	0,19	0,14	0,08	0,03	0	85	

Ciśnienie zasilania MPa	Zużycie powietrza NI/s	Czas opróżniania (s/l) dla różnych poziomów próżni (-kPa)											Maksymalne podciśnienie -kPa
		10	20	30	40	50	60	70	80	90			
0,5	1,02	0,23	0,49	0,79	1,16	1,61	2,21	3,013	4,96	0	85		

Rysunki wymiarowe

